

**Description:** RX-16T-KD LED tube KIT. Use 5H straw hat LED or 5R spotlight LED. PC tube, chrome plated plug, supporting high-efficiency power supply, suction cups and screw. Attractive appearance, easy to install. Mainly used for: aquarium, fish tank, home decorative lighting DIY.


**Features:**

- Energy efficient, environmentally friendly, no harmful UV, mercury
- Plug chrome plating, the appearance of fine
- LED tube Waterproof, protection class IP67
- Especially with suction cups, can be adsorbed on the glass surface, easy to install
- long service life over 30,000 hours
- Colors: red, green, blue, white, warm white, yellow, pink, purple and combinations
- Optional LED Type: 5H straw hat LED, 5R spotlight LED


**Mechanical Specifications:**

Main Material: PC tube, LED, PCB, cable, suction cups, screws, power supply

Tube diameter: 16mm

Optional tube length: 15cm, 20cm, 30cm

Power Dimension: 78x73x30mm (CE), 63x33x23mm (PSE, UL)

Temperature: -20 °C ~ 50 °C

Weight: see table below

**Electronical Specifications:**

LED tube input voltage: DC12V

LED Power Supply Input Voltage: 100VAC, 230VAC

Power: 0.1W (with power)

LED parameter: the table below

RX-16T-KD Tube light data sheet

MODEL	TUBE Length	TUBE QTY	LED QTY	LED TYPE	LED COLOR	POWER	Packing list	Weight (including power supply)
RX-16T10-KD15	15cm	2pcs	18pcs	5H hat LED 120° 5R spotlight LED 20° Or a combination of the above two LED	Red, green, blue, white, warm white, yellow, pink, purple	2W	LED driver	180 g
RX-16T10-KD20	20cm	2pcs	30pcs			3W	1pcs	220 g
RX-16T10-KD30	30cm	2pcs	48pcs			5W	screw4pcs	260 g
							4pcs	
RX-16T20-KD30	30cm	2pcs	24pcs			2.5W	LED tube 2pcs	250 g



Note:

The table contains the CE certification weight of power supply, such as the use of UL PSE certification power to reduce the weight of 25g



Optional LED model and color:

Model Number	Dimension	Lens diffused	Wavelength color temperature Light Output (mcd /IF=20mA)								Viewing Angle (degrees)	Max. Power (W)
			625nm	525nm	460nm	590nm		400nm	6500k	3200k		
5R LED	Φ5x8.7	clear	4000	20000	6000	6000	800	100	25000	19000	20°	0.07
5H LED	Φ5x4.8	clear	400	1500	1200	1500	120	10	2000	2000	120°	0.07

Dimension:



American standard, Japanese standard LED power supply regulations (UL, PSE certification)



European regulatory standard LED power supply (CE)

LED standard on the hybrid alignment:



**BWRBWRBWRBWRBWRBWRBWRBWR**



**WBWBWBWB**

5H straw hat LED, use the black color word, for example as: B represents a blue 5H straw hat LED.

5R spotlight LED, with a color word, for example: R represents red 5R spotlight LED

Note:

1. Cut off the power before installation, ensure the switch is closed, to prevent electric shock.
2. To avoid the installation of the heat source and hot steam, corrosive gas, so as not to affect life expectancy.
3. This product is part of the water level of the lamp IP67, please note that the waterproof connector plug

Warning Description:

Open the product should immediately check the product packaging is intact. Requirements or specifications appear in non-human caused failure, retreat retailers or directly return to factory replacement. If long-term disabled should be stored in a cool, dry, clean environment, the prohibition in the humid, high temperatures or flammable and explosive places in the storage and use. Not disassemble, replace the device. Product improvements or other reasons due to parameter change without notice.